



## Interlock Anti-tilt : Safety Guidelines

Anti-tilt prevents the access of two or more pull-out accessories simultaneously.

It is essential that when two or more pull-out accessories (except MRS reference shelves) are fitted in a unit, Triumph's interlocking mechanism is fitted to link all the pull-out accessories. It is not recommended to fit pull-out accessories above more than 50% of the unit height and up to a maximum of four vertical cradles in the taller units.

- The lowest accessory should be fitted as close to the base of the unit as possible.
- Never stand or lean on an extended pull-out accessory.
- Always ensure the units are positioned on a level floor.
- The levelling feet are properly adjusted to make the unit stable
- Wherever possible units are secured to a structurally suitable wall, or to the back of another unit.
- Pull-out accessories are fitted correctly as detailed in the note above.
- Recommended evenly distributed load bearings are not exceeded.
- The unit is not configured or loaded in a way that could cause it to become unstable in use.
- The above does not apply to product reference MRS when used as a reference shelf.

Triumph accepts no responsibility for damage caused by not following the manufacturers recommended safety guidelines.

## Metrix and Everyday : Interlock Anti-tilt options



Code	Description
------	-------------

Filing drawer MFD (CD Rack) allowing 25mm above drawer height  
Fixed distance 150mm between drawers

INT15D6	Allows maximum of 6 drawers
INT15D5	Allows maximum of 5 drawers
INT15D4	Allows maximum of 4 drawers
INT15D3	Allows maximum of 3 drawers
INT15D2	Allows maximum of 2 drawers

Filing drawer MFD (Lloyd George medical wallet) allowing 100mm above drawer height  
Fixed distance 225mm between drawers

INT22D5	Allows maximum of 5 drawers
INT22D4	Allows maximum of 4 drawers
INT22D3	Allows maximum of 3 drawers
INT22D2	Allows maximum of 2 drawers

Vertical cradle MPCR and pockets  
Fixed distance 275mm between cradles

INT30D4	Allows maximum of 4 cradles
INT30D3	Allows maximum of 3 cradles
INT30D2	Allows maximum of 2 cradles



Description	Maximum number of pull-outs used	Fixed distance
-------------	----------------------------------	----------------

Filing drawer (MFD)	6	150mm
Filing drawer (MFD)	5	225mm
Vertical cradle (MPCR)	4	275mm

Description	Number of slots from base	Number of slots after
-------------	---------------------------	-----------------------

Filing drawer (MFD)	8	6
Filing drawer (MFD) (with Lloyd George wallets)	8	9
Vertical cradle (MPCR)	10	11

